## 20 Lindsay Road Cambridge, ON N1R 7K6 Tel: 519-653-6000 ext. 222

Fax: 519-653-1016 info@verigreen.ca www.verigreen.ca

## XLERATOR® HAND DRYERS



Model XL-BW Surface-Mounted Automatic Hand Dryer White Thermostat (BMC) Cover



Model XL-W Surface-Mounted Automatic Hand Dryer White Epoxy Painted Cover



**Model XL-GR** Surface-Mounted Automatic Hand Dryer **Graphite Textured** Painted Cover



Model XL-C Surface-Mounted **Automatic Hand Dryer** Chrome Plated Cover



Model XL-GR Surface-Mounted Automatic Hand Dryer Stainless Steel Cover - Brushed

## **Features**

- Dries hands COMPLETELY in 10 to 15 seconds
- Uses 80% less energy versus other dryers
- 95% cost savings versus paper towels
- GREENSPEC® approved and helps qualify for LEED® credits
- Source reduction alternative
- Promotes better hygiene
- Stocked in 208V and 220V in white. Special order in the graphite textured paint, Thermoset BMC, Brushed stainless steel and chrome plate in 208V and 220V
- Runs on 15A service (great for older buildings)
- Hand dryer cover is one-piece, heavy-duty, rib-reinforced, die-cast zinc alloy. It is lightweight, unbreakable, rustproof and all exposed surfaces are bright chrome plated or finished with chip-proof, electrostatically applied epoxy paint. Fastened to a wall plate by two chrome plated, tamper-proof bolts.
- The hand dryer motor is a commutated, through-flow, discharge vacuum motor/blower (5/8HP, 20,000RPM) which provides air velocity of 16,000 LFM (linear feet per minute) at the air outlet and 14,000 LFM at the hands (4 inches [102mm] below air outlet).
- The hand dryer heating element (900W) is constructed of Nichrome wire and mounted inside the blower housing, thereby being vandal proof. It is protected by an automatic resetting thermostat. The Xlerator® series will produce an air temperature of up to 135°F (57°C) at a 72°F (22°C) ambient room temperature at the hands (4 inches [102mm] below air outlet).
- The Xlerator® control assembly is activated by an infrared optical sensor located next to the air outlet. The dryer will operate as long as hands are under the air outlet. There is a 35-second shut off safety feature if hands are not removed.
- ADA compliant recess kits also available.
- Limited Warranty The hand dryer is guaranteed to be free from defects for a period of five (5) years. Warranty shall include factory performed labour as well as the repair or exchange of defective parts, at manufacturer's option.